



Leeway II™

Water Conditioning Agent / Nonionic Surfactant / Humectant / Drift Reduction Agent

GENERAL INFORMATION

Leeway II is a drift reduction and water conditioning agent formulated specifically for reducing off-target drift.

Leeway II imparts a neutral pH.

Leeway II can eliminate antagonism of the spray tank caused by hard water minerals such as calcium, iron and magnesium.

The surfactant ingredient in Leeway II improves spray droplet spreading and penetration into the targeted leaf surface.

Leeway II provides humectancy to spray droplets resulting in a slower drying time for enhanced uptake of active ingredients.

Leeway II can be used for a wide range of pesticide and nutrient spray mixtures when accompanying labels recommend water conditioners and spreader-wetter adjuvants.

USE RATES

Ground/Aerial for Water Conditioning/Buffering: Use 1 to 4 quarts per 100 gallons of spray mixture.

For General Use as a Drift Reduction Agent: Use 1 to 3 quarts per 100 gallons in the spray mixture.

TECHNICAL INFORMATION

Net Weight: 9.59 lbs/gal

Specific Gravity: 1.12-1.15

Flashpoint: >200°F SFCC

pH: 5.8-7.5 (neat)

Solubility in Water at 20°C: Dispersible

Color & Appearance: Slightly Hazy to Hazy Colorless Liquid

Storage Temperature - Minimum: 40°F

Storage Temperature - Maximum: 120°F

DOT/IMDG Transportation: Not Regulated

Registered With CDPR: No

Registered With WSDA: Yes

PRINCIPAL FUNCTIONING AGENTS

Trisodium citrate dihydrate,
alkyl polyglucoside C9-11,
diethylene glycol.....34.75%



PACKAGING

2 x 2.5 gallon jugs
36 cases per pallet
Item#: LWYII02

265 gallon tote
1 tote per pallet
Item#: LWYII265



KALO

Leeway II is a trademark of KALO, Inc.
KALO, Inc., 13200 Metcalf Ave. Suite 250, Overland Park, KS 66213 • www.kalo.com
Important: This information is not a substitute for the label. Always read and follow label

Document Date: 03.28.2025
© 2025 KALO, Inc.